



AMULET® TA (Transparent Armor) Ballistic Barrier – Data Sheet

Product Name: AMULET® TA Rifle

Product ID: APT-A3-RIFLE

Ballistic Threat Rating: NIJ 0108.01 Armor Type I- III RIFLE PROTECTION
UL-752 Rating Level 1 – 8, EN1063 Level BR6

Nominal Thickness: 01.1875 inch/ 30.1625 cm

Average Weight: 10.20lbs/sq. ft. /4.63 Kg/m²

Sizes available: Largest: 70" x 132" Minimum 36"x36"

Structure: Rigid

Performance Benefits: Tested and Compliant to meet NIJ standards, lightweight, ease of installation with standard tools & equipment, multiple-hit capacity, non-ricochet.

Applications: Commercial Systems Furniture, Modular Floor to Ceiling Walls, Architectural Walls, Millwork, Signage, Doors, Boats and Ships, Aircraft, Land Vehicles.

PRODUCT	TEST CRITERIA/ PERFORMANCE LEVEL	BALLISTIC DATA	NOMINAL THICKNESS	PSF Kg/m ²
Amulet® 3 Rifle Protection	UL 752/Level 1	9mm, 124 Gr., 1175 fps, FMJ	0.890-0.950 inch 22.60- 24.13mm	4.2 PSF 20.5 Kg/m ²
	UL 752/Level 2	357 Mag. 158 Gr., 1250 fps, LSP		
	UL 752/Level 3	44 Mag. 240 Gr., 1350 fps, SWG		
	UL 752/Level 4	.30 Cal., rifle 180 Gr., 2540 fps, LCSP		
	UL 752/Level 5	7.62mm rifle 150 Gr., 2750 fps, LCFM CJ., MB		
	UL 752/Level 6	9mm, 124 Gr., 1400 fps, FMJ		
	UL 752/Level 7	5.56mm rifle 55 Gr., 3080 fps, LCFM CJ		
	UL 752/Level 8	7.62mm rifle 150 Gr., 2750 fps, LCFM CJ., MB		
	NIJ 0108/Level III	7.62mm rifle 150 Gr., 2750 fps, LCFM CJ., MB		