

## AMULET® 1 Ballistic Barrier – Data Sheet

**Product Name:** AMULET® 1 Handgun Protection

**Product ID:** APT-A1-HANDGUN

**Ballistic Threat Rating:** National Institute of Justice (NIJ) 0108.01 Armor Type I-III A  
UL-752 Rating Level 1, 2, 3 & 6

**Nominal Thickness:** 0.21 inch/5.33 mm

**Average Weight:** 1.3 lbs per sq ft

**Sizes available:** 48" x 96" or custom sizes

**Structure:** Moldable/Flexible, Rigid when cured

**Performance Benefits:** Tested and Compliant to NIJ standards, UL752 Level 3, lightweight, moldable, ease of installation with standard tools & equipment, multiple-hit capacity, non-ricochet.

**Applications:** Commercial Furniture: Seating, Desks, Panel & Tile Office Systems, Modular Walls, Architectural Walls, Custom Millwork, Doors.

AMULET® 1 BALLISTIC BARRIER - HANDGUN PROTECTION					
TEST CRITERIA/ PERFORMANCE LEVEL	THREAT	NOMINAL BULLET MASS	REQUIRED BULLET VELOCITY	REQUIRED HITS PER ARMOR SAMPLE	PERMITTED PENETRATIONS
NIJ Level IIIA	44 Magnum Lead Semi-Wadcutter Gas Checked	15.6 gram 240 grain	426 +/- 15 m/s 1400 +/- 50 ft/s	5	0
	9mm Full Metal Jacket w/Lead Core	8.0 gram 124 grain	426 +/- 15 m/s 1400 +/- 50 ft/s	5	0
UL 752- Level 1	9mm Full Metal Jacket w/Lead Core	8.0 gram 124 grain	1175 ft/s min 1293 ft/s max	3	0
UL 752- Level 2	.357 Magnum Lead Soft Point	10.2 gram 158 grain	1250 ft/s min 1375 ft/s max	3	0
UL 752- Level 3	44 Magnum Lead Semi-Wadcutter Gas Checked	15.66 gram 240 grain	1350 ft/s min 1485 ft/s max	3	0
UL 752- Level 6	9mm Full Metal Jacket w/Lead Core	8.0 gram 124 grain	1400 ft/s min 1540 ft/s max	5	0