

## AMULET<sup>®</sup> 1 Ballistic Barriers – Data Sheet

<b>Product Name:</b>	AMULET <sup>®</sup> 1 Ballistic Barriers
<b>Product ID:</b>	BFS-A1-III A
<b>Ballistic Threat Rating:</b>	NIJ 0108.01 Armor Type I-III A HANDGUN PROTECTION UL-752 Rating Level 1, 2, 3 & 6
<b>Nominal Thickness:</b>	0.21 inch/5.33 mm
<b>Average Weight:</b>	1.3 lbs per sq ft
<b>Sizes available:</b>	48" x 96" and custom size cuts
<b>Color/Structure:</b>	Yellow/Moldable, Rigid when cured
<b>Performance Benefits:</b>	Certified to exceed NIJ standards, lightweight, moldable, ease of installation with standard tools & equipment, multiple-hit capacity, non-ricochet.
<b>Applications:</b>	Commercial Furniture: Seating, Desks, Panel & Tile Office Systems, Modular Walls Architectural Walls, Millwork, Signage, Doors.

PRODUCT	TEST CRITERIA/ PERFORMANCE LEVEL	BALLISTIC DATA	NOMINAL THICKNESS	PSF
Amulet <sup>®</sup> Series I Ballistic Barriers  Handgun Protection	UL 752/Level 1	9mm, 124 Gr, 1175 fps, FMJ	0.21 inch	1.31
	UL 752/Level 2	357 Mag. 158 Gr, 1250 fps, LSP		
	UL 752/Level 3	44 Mag. 240 Gr, 1350 fps, SWG		
	UL 752/Level 6	9mm, 124 Gr, 1400 fps, FMJ	5.33 mm	
	NIJ 0108/Level III A	44 Mag. 240 Gr, 1400 fps, SWC		