

AMULET® 2 Ballistic Barriers – Data Sheet

Product Name:	AMULET® 2 Ballistic Barriers HANDGUN PROTECTION
Product ID:	BFS-A2-IIIA
Ballistic Threat Rating:	NIJ 0108.01Armor Type I-III A UL-752 Rating Level 1, 2, 3 & 6
Nominal Thickness:	0.185-0.202 inch/4.935-5.080 mm
Average Weight:	0.91 lbs per sq ft
Sizes available:	48" x 96" and custom size cuts
Color/Structure:	White/Rigid
Performance Benefits:	Certified to exceed NIJ standards, lightweight, moldable, ease of installation with standard tools & equipment, multiple-hit capacity, non-ricochet.
Applications:	Commercial Furniture: Seating, Desks, Panel & Tile Office Systems, Modular Walls, Architectural Walls, Millwork, Signage, Doors.

PRODUCT	TEST CRITERIA/ PERFORMANCE LEVEL	BALLISTIC DATA	NOMINAL THICKNESS	PSF
Amulet® 2 Ballistic Barriers Handgun Protection	UL 752/Level 1	9mm, 124 Gr, 1175 fps, FMJ	0.185-0.202 inch	0.91
	UL 752/Level 2	357 Mag. 158 Gr, 1250 fps, LSP		
	UL 752/Level 3	44 Mag. 240 Gr, 1350 fps, SWG		
	UL 752/Level 6	9mm, 124 Gr, 1400 fps, FMJ	4.935-5.080 mm	
	NIJ 0108/Level IIIA	44 Mag. 240 Gr, 1400 fps, SWC		