



AMULET® 3– Data Sheet

Product Name: AMULET® 3

Product ID: APT-A3-RIFLE

Ballistic Threat Rating: NIJ 0108.01 Armor Type I- III RIFLE PROTECTION
UL-752 Rating Level 1 –7

Nominal Thickness: 0.65 +/- 0.09 inch

Average Weight: 3.3lbs/sq. ft. +/- 0.1 lbs.

Sizes available: 50” x 63”

Structure: Rigid

Performance Benefits: Tested and Compliant to meet both NIJ and UL 752 standards, lightweight, ease of installation with standard tools & equipment, multiple-hit capacity, non-ricochet.

Applications: Commercial Systems Furniture, Modular Floor to Ceiling Walls, Architectural Walls, Millwork, Signage, Doors, Boats and Ships, Aircraft, Land Vehicles.

| PRODUCT | TEST CRITERIA/ PERFORMANCE LEVEL | BALLISTIC DATA | NOMINAL THICKNESS | PSF |
|--|--|--|----------------------|----------|
| Amulet® 3 Rifle Protection | UL 752/Level 1 | 9mm, 124 Gr., 1175 fps, FMJ | 0.65 inch | 3.3 lbs. |
| | UL 752/Level 2 | 357 Mag. 158 Gr., 1250 fps, LSP | | |
| | UL 752/Level 3 | 44 Mag. 240 Gr., 1350 fps, SWG | | |
| | UL 752/Level 4 | .30 Cal., rifle 180 Gr., 2540 fps, LCSP | | |
| | UL 752/Level 5 | 7.62mm rifle 150 Gr., 2750 fps, LCFMCJ., MB | | |
| | UL 752/Level 6 | 9mm, 124 Gr., 1400 fps, FMJ | | |
| | UL 752/Level 7 | 5.56mm(.223 Cal) Rifle 55 Gr.,3080 fps, LCFMCJ | | |
| | NIJ 0108/Level III | 7.62mm (.308) rifle 150 Gr., 2800 fps, FMCJ., MB | | |