

AMULET® 3 Ballistic Barrier – Data Sheet

Product Name:	AMULET® 3 Ballistic Barrier
Product ID:	BFS-A3-III
Ballistic Threat Rating:	NIJ 0108.01Armor Type I- III RIFLE PROTECTION UL-752 Rating Level 1 - 8
Nominal Thickness:	0.890-0.950 inch/22.60-24.13mm
Average Weight:	4.2lbs/sq. ft. /20.50 Kg/m2
Sizes available:	Custom cut per order or maximum sheet size: 48” x 96”
Color/Structure:	White/Rigid
Performance Benefits:	Certified to exceed NIJ standards, lightweight, ease of installation with standard tools & equipment, multiple-hit capacity, non-ricochet.
Applications:	Commercial Systems Furniture, Modular Floor to Ceiling Walls, Architectural Walls, Millwork, Signage, Doors, Boats and Ships, Aircraft, Land Vehicles.

PRODUCT	TEST CRITERIA/ PERFORMANCE LEVEL	BALLISTIC DATA	NOMINAL THICKNESS	PSF Kg/m2
Amulet® Series III Ballistic Barriers Rifle Protection	UL 752/Level 1	9mm, 124 Gr., 1175 fps, FMJ	0.915-0.980 inch 22.60- 24.13mm	4.2 PSF 20.5 Kg/m2
	UL 752/Level 2	357 Mag. 158 Gr., 1250 fps, LSP		
	UL 752/Level 3	44 Mag. 240 Gr., 1350 fps, SWG		
	UL 752/Level 4	.30 Cal.,rifle180 Gr., 2540 fps, LCSP		
	UL 752/Level 5	7.62mm rifle150 Gr., 2750 fps, LCFMCI., MB		
	UL 752/Level 6	9mm, 124 Gr., 1400 fps, FMJ		
	UL 752/Level 7	5.56mm rifle 55 Gr.,3080 fps, LCFMCI		
	UL 752/Level 8	7.62mm rifle150 Gr., 2750 fps, LCFMCI., MB		
	NIJ 0108/Level III	44 Mag. 240 Gr., 1400 fps., SWC		