

AMULET[®] 3LT Ballistic Barrier – Data Sheet

Product Name:	AMULET [®] 3LT Ballistic Barrier		
Product ID:	BFS-AS3LT-III		
Ballistic Threat Rating:	NIJ 0108.01Armor Type I- III	RIFLE PROTECTION	
	UL-752 Rating Level 1 - 8		
Nominal Thickness:	0.65inches /16.51mm		
Average Weight:	3.3 lbs/sq ft / 16.11 Kg/m ²		
Sizes available:	Custom cut per order or maximum sheet size: 63"x 50"		
Color/Structure:	White/Rigid		
Performance Benefits:	Lightweight, ease of installation with standard tools & equipment, multiple-hit capacity, non-ricochet.		
Markets Served:	Airports, Corporate Offices, Government, Healthcare, Municipal, VIP residences, Sensitive Compartmented Information Facilities (SCIFs).		
Applications:	Architectural Walls, Permanent Signage, Custom Millwork, Doors, Boats and Ships, Aircraft, Land Vehicles.		

PRODUCT	TEST CRITERIA/ PERFORMANCE LEVEL	BALLISTIC DATA	NOMINAL THICKNESS	PSF Kg/m ²
Amulet [®] 3LT Ballistic Barriers Rifle Protection	UL 752/Level 1	9mm, 124 Gr., 1175 fps, FMJ	0.65 inch 16.51mm	3.3 PSF 16.1Kg/ m ²
	UL 752/Level 2	357 Mag. 158 Gr., 1250 fps, LSP		
	UL 752/Level 3	44 Mag. 240 Gr., 1350 fps, SWG		
	UL 752/Level 4	.30 Cal.,rifle180 Gr., 2540 fps, LCSP		
	UL 752/Level 5	7.62mm rifle150 Gr., 2750 fps, LCFMCJ., MB		
	UL 752/Level 6	9mm, 124 Gr., 1400 fps, FMJ		
	UL 752/Level 7	5.56mm rifle 55 Gr.,3080 fps, LCFMCJ		
	UL 752/Level 8	7.62mm rifle150 Gr., 2750 fps, LCFMCJ., MB		
	NIJ 0108/Level III	44 Mag. 240 Gr., 1400 fps., SWC		